

Supporto Antifessura

Polyester non-woven anti-crack reinforcement

Presentation

Supporto Antifessura is a special tape made of 150 g/m² non-woven polyester, about 1 mm thick. It comes in 50 m rolls and can be 1 m, 50 cm and 25 cm wide. For **DIY** and **small repair works**, use the 10 m x 25 cm rolls.

The **Supporto Antifessura** reinforcement looks like a very soft material that perfectly adapts to any shape and surface (including wavy ones like fibre cement or metal roof tiles).

Applications

Use **Supporto Antifessura** to reinforce our bituminous elastomeric water-based liquid membrane, **ElastiK**, which has many applications, including:

- waterproofing visible surfaces that are not to be covered with tiles or concrete screeds (for these, use the 1 m rolls);
- repairing welds between sheets of bituminous membranes (for these, use the 25 cm wide rolls);
- repairing cracks in fibre cement or metal covering sheets (for these, use the 25 cm wide rolls).

Operating instructions

Do not apply **ElastiK** on the surface first and, after a few minutes, apply the non-woven polyester **Supporto Antifessura**: **ElastiK** would dry up immediately and the **Supporto Antifessura** would not stick. Instead:

- 1) Place the **Supporto Antifessura** roll on the surface to treat.
- 2) Apply a strip of **ElastiK** in front of the roll, using a large brush. Then, on the fresh product, immediately apply the **Supporto Antifessura** reinforcing support, pressing it with your feet or a brush to help **ElastiK** penetrate into the fabric.

Warnings

Supporto Antifessura can be preserved for a long time if kept in its original package and out of direct sunlight.

Rev. 01/01/2014